LXL GATE OPERATORS

Commercial, Industrial and High Security

Our line of hydraulic slide gate operators is suitable for most applications. The LXL Gate Operator is a robust system for high cycle applications.



Features

- More secure than chain-drive units
- Low maintenance, self-contained hydraulic system with minimal wear items
- Safe 24VDC controls standard
- Drive rail increases rigidity of gate panel
- Continuous duty operation
- Hand release for manual operation
- Built-in maximum run timer and timer to close
- On board 3 button control station
- On board LCD display for programming and diagnostics
- Standard voltages & phases
- Customer/Tech Support

UL CERTIFIED
SAFETY US E363069

★★★ MADE IN USA

Accessories

- Drive rails (14' lengths)
- Riser pedestal (required for Ameristar Gates)
- Cold weather package (ice and snow scrapers)
- Heater

Contact your salesperson for additional accessories.

NOTE: Customer request for other accessories or manufacturers, to be sourced by customer.

Tested UL325 Entrapment Protection Devices

Type B1 Non-contact Sensors (Photo Eye)

- EMX Industries Model IRB-MON
- Omron Model E3K-R10k4
- Miller Edge OptiGuard OG-T-K10
- Miller Edge TruGuard TG-R-K10

Type B2 Contact Sensors

- Miller Edge Sensing Edges—all models with a T2 resistive termination
- Miller Edge Wireless Monitored Transmitter/ Receiver Kit Model RB-G-K10
- Miller Edge Multi-Input Module Model MIM-62
- EMX WEL-200 Edge Link

Plug-in Loop Detectors

NOTE: Customer request for other manufacturers or manufacturers, to be sourced by customer.



B&B ROADWAY & SECURITY SOLUTIONS

ASSA ABLOY

1.800.367.0387 | BBRSS.COM

LXL GATE OPERATOR SPECIFICATIONS

LXL SERIES GATE OPERATORS ARE BACKED BY A FIVE-YEAR LIMITED FACTORY WARRANTY.

CLASS OF OPERATION	Model LXL - UL 325 Class I, II, III, IV
TYPE OF GATE	Vehicular Slide Gates Only
DRIVE SYSTEM	Hydraulic with Aluminum Drive Rail
DUTY	Continuous
SPEED	1 ft. per second
ENTRAPMENT PROTECTION	Primary — Inherent entrapment sensing system (Type A)
	Secondary — Provisions for connection of a monitored non-contact sensor (Type B1) and/or a monitored contact sensor (Type B2)

AVAILABLE MODELS	VOLTAGE	PHASE	AMPS	MAX GATE WEIGHT	MAX GATE OPENING	INSTALL CLASS	TRAVEL SPEED	DUTY CYCLE RATING	UNIT WEIGHT
LXL-3001-1151	115	1	16	3000	90	I-IV	1.0ft/s	Continuous	250
LXL-3001-2301	208/230	1	8	3000	90	I-IV	1.0ft/s	Continuous	250
LXL-3001-2303	208/230	3	4	3000	90	I-IV	1.0ft/s	Continuous	250
LXL-3001-4603	460	3	2	3000	90	I-IV	1.0ft/s	Continuous	250

NOTE: Drive Rail (14' length standard; includes splice and hardware)
Pedestal Riser (12" high, required for Ameristar gates)



Contact your salesperson today to make the switch to an automatic operator!

B&B ROADWAY & SECURITY SOLUTIONS

ASSA ABLOY

1.800.367.0387 | BBRSS.COM

#B&B-5 | 07/2024